

Elite-CVD-7B

Cost-effective Built-in 7" Control System



Main Features

Wired built-in touch panel touchCUE-7-B

- 7" a-Si TFT display 1 280 x 800 pixels, pixel density 217 ppi
- Projected capacitive touch overlay, edge-to-edge front glass
- Video preview
- Wired Ethernet connection, PoE IEEE 802.3af compatible
- Aluminium slim unibody enclosure
- Compatible with European/UK 1-gang electrical boxes

Controller controlCUE-versatile-d

- Control ports - 8x versatile, 3x bi-directional serial RS-232/485
- Wired Ethernet connection
- Power supply 24 VDC or Power over Ethernet (PoE)
- DIN rail plastic enclosure, width 4 modules

Description


This control package allows to create cost effective complete control solution based on wired built-in touch panel and DIN rail controller.

The touchCUE-7-B is wired built-in touch panel offering clean modern design with edge-to-edge front glass and sleek aluminium body. It is ideal front-end for any built-in applications. The 7" a-Si TFT touch screen display offers resolution 1 280 x 800 pixels and it produces stunning true color images. Touch panel has projected capacitive touch overlay. Single cable Ethernet connection provides easy network integration. The touch panel is equipped with Power over Ethernet (PoE) technology enabling an Ethernet network cable to deliver both data and power. The touch panel installs easily over a 1-gang standard European/UK electrical box. It can

also be attached directly to drywall and other surfaces over the front of cutout. When installed it protrudes only 13 mm from the mounting surface.

The DIN rail compatible controller controlCUE-versatile-d is fully functional IP controller with eight versatile ports and three bi-directional serial RS-232/485 control ports. Fully compatible with CUE touch panels, this controller can work as standalone device. The versatile port is a new type of control port and depending on the application each versatile port can be used as an input or output. Single cable Ethernet connection provides easy network integration and the controller is equipped with Power over Ethernet (PoE) technology enabling an Ethernet network cable to deliver both data and power.

Application Diagram



Box Contents

- Tabletop touch panel touchCUE-7-B
- Controller controlCUE-versatile-d
- Connector set
- Ethernet cables
- 2x IR Adapter /i
- Power supply with PoE injector
- DIN rail power supply 24 VDC / 24 W
- Cleaning tissue
- Declaration of Conformity
- Data Sheet
- Cue System Connector Wiring Sheet

Order Information

Product code ST0071

Specifications

For device specifications see appropriate product cut sheets.